


onferLink CL-800 is a standalone teleconference bridge that is connective with 8 analog lines coming from Central Office or behind PBX so as to have the capability of connecting a maximum of 8 people in a virtual meeting room for conducting an audio conference meeting or seminar remotely. Two units of CL-800 can be wired together through an existing telephone circuit port in order to expand the capacity of allowing a maximum of 14 people staying in a same virtual meeting room and converse each other there.

ConferLink CL-800 provides secure, plug-n-play audio conferencing solution that works right out of the box without complicated setup. The solution does not require use of third-party provider and is internal to enterprise, ensuring sensitive conversations remain within enterprise.


For participation of a regular meeting, invited persons can voluntarily call to CL-800 on prescheduled date and time. For holding a last-minute meeting or forcefully inviting persons to join the meeting, the organizer can call from the virtual conference room of CL-800 to the target persons.



Many teleconference participants are actually from within the organization. Using CL-800, calls of these participants can be free. For the participants from outside the organization, they simply pay the same phone bill as they pay for normal phone calls.



By default the organizer uses the 0-9, \* and # buttons of a touch-tone phone to manage the conference room and meeting activity. If optional Discuss (computer software) and N-port (a small hardware enabling connection between CL-800s and computer) are installed, the organizer can instead use computer keyboard and mouse to manage the room and activity.



## **KEY FEATURE LIST**

## CL-800

- Plug and play: Once phone line connection is done, it is ready for servicing participants.
- Meet-me style conference: Participants can voluntarily join the meeting at prescheduled date and time.
- Last-minute style conference: Organizer can call from the meeting room forcefully inviting participants to join.
- Security lock: Organizer can lock/unlock meeting room to prevent/invite additional participant for participation.
- Password protection: Administrator, organizer and participants are given with a different password.

- Participant screening control: Joining a meeting needs password authentication.
- Entry and exit tones: Distinct entry and exit tones announce the arrival and departure of each participant.
- Audio announcement of room-full: The voice prompt "... room is full" if the organizer is attempting to call from the room to invite excessive participant to join the meeting.
- Multilingual meeting guidance: Voice prompts in Chinese, English or Japanese are available.
- Audio helps: Participants can activate audio guidance whenever needed.

#### **DISCUSS**

- Graphical interface for operation
- Ports status (idle or occupied) indicated dynamically by graph
- Attendance authenticated by ID and password
- Conference room locked and unlocked
- Capable to call from meeting room for forcefully inviting participants to join
- Group calls can be placed for automation of forcefully inviting multiple participants to join
- Having encountered ring-no-answer or busy condition, calls can be redialed automatically

# **SPECIFICATIONS**

### **CL-800**

- Telephone interfaces: 2-wire analog (Central Office or behind PBX)
- Dial and configuration signal: DTMF 0-9, \* and #
- Capacity: 8 ports
- Power Input: AC 12V 1A
- Main Body Dimensions: 200 mm x 150 mm x 15 mm
- Net Weight: 890g
- Working Temperature: 5-40°C
- Humidity: 20-80%

#### **DISCUSS**

- System requirement: PC running Windows 2000/XP with at least 5MB free hard disk space.
- Network adapter: N-Port x 1
- Connection cables: Factory-supplied cables



E-mail: info@multisuns.com